



# PowerLine-Laser G360P Multi-18V




Green cross-line laser with horizontal laser circle, vertical laser line as well as upper and lower laser points – compatible with 18 V battery systems from well-known manufacturers

This green cross line laser projects a horizontal laser circle and vertical laser line, ideal for precisely aligning objects. The top and bottom plumb points allow simultaneous work on floors and ceilings. Thanks to the green laser technology with the PowerGreen++ brightness classification, the best visibility is ensured also in poor lighting conditions. Thanks to the PowerAdapter available separately, the laser is compatible with the 18V battery systems from well-known manufacturers. This means that the user can perfectly integrate the laser in their existing tools, for seamless and efficient use.

- Precise alignment with a horizontal laser circle and a vertical line arranged at right angles to it
- Compatibility with 18V battery systems: Works with 18V batteries from various well-known manufacturers thanks to separately available PowerAdapters
- Efficient use: By choosing the right adapter, the laser can be seamlessly integrated in the customer's existing 18V peripheral systems
- Easy alignment of slopes with manual tilt function
- Individually switchable laser lines
- Plumb function for synchronous working on floor and ceiling
- MicroControl: High-precision adjustment of the vertical laser lines via lateral fine adjustment without having to move the laser itself

## TECHNICAL DATA

<b>Self-levelling Range</b>	± 3.5° (horizontal)
<b>Accuracy</b>	±0.2 mm/m
<b>Levelling</b>	horizontal / vertical automatic
<b>Visibility (Typical)*</b>	60 m
<b>Laser Wavelength</b>	515 nm
<b>Laser Class</b>	2 / < 1 mW
<b>Power Supply</b>	Power pack 5V / DC / 2A for continuous operation
<b>Operating Time</b>	with 18V system 2 Ah approx. 10hr. with 18V system 4 Ah approx. 20hr.
<b>Operating Conditions</b>	-10°C ... 50°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level
<b>Storage Conditions</b>	-10°C ... 70°C, max. humidity 80% rH
<b>Dimensions (W x H x D)</b>	163 mm x 158 mm x 93 mm
<b>Weight</b>	800 g (without accessories)
	* at max. 300 lux



## SCOPE OF DELIVERY



Item No. 036.360L      GTIN (EAN) 4021563744596      SU 1