

## PocketPlane-Laser 3G



Three-dimensional, practical laser with one horizontal and two vertical green laser circles and a comprehensive range of accessories – a versatile tool for demanding projects

This three-dimensional, practical and highly visible green laser projects one horizontal and two vertical laser circles for precise alignment of objects. The laser crosses form a plumb function for working simultaneously on floors and ceilings. A manual slope mode is available for creating gradients. This laser is a particularly useful tool for demanding projects due its the comprehensive range of accessories. The PocketWallHolder is a multi-functional, height-adjustable, magnetic bracket for attaching the laser to walls, metal items and tripods with a 1/4" or 5/8" thread.

- Three-dimensional laser with a horizontal and two vertical 360° laser circles
- Accurate horizontal and vertical alignment of objects
- Good visibility through green laser technology
- Easy alignment of slopes with manual tilt function
- Plumb function for synchronous working on floor and ceiling
- Height-adjustable, magnetic, multi-function bracket with 1/4" and 5/8" thread for attaching to walls, metal items and tripods
- Magnetic target plate with stand, nail hole and dual scale – perfect for working close to ceilings



### TECHNICAL DATA

<b>Self-levelling Range</b>	± 3.5° (horizontal)
<b>Accuracy</b>	± 0.3 mm / m
<b>Levelling</b>	automatic
<b>Visibility (Typical)*</b>	30 m
<b>Laser Wavelength</b>	515 nm
<b>Laser Class</b>	2 / < 1 mW (EN 60825-1:2014/ A11:2021 / EN 50689:2021)
<b>Length of Receiver Unit</b>	0 mm
<b>Power Supply</b>	Li-ion battery pack 3.7V / 3.6Ah / 13.32Wh Power adapter 5V/DC / 2A
<b>Operating Time</b>	with 3 laser levels: approx. 9 hours
<b>Operating Conditions</b>	0°C ... 50°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level
<b>Storage Conditions</b>	-10°C ... 70°C, max. humidity 80% rH
<b>Dimensions (W x H x D)</b>	104 mm x 97 mm x 76 mm x #
<b>Weight</b>	388 g (incl. battery pack)

Optional: CombiRangeXtender 40

Artikel-Nr.: 033.35A

max.  
40 m



### SCOPE OF DELIVERY



Item No. 036.700A

GTIN (EAN) 4021563724574

SU 1