



## SmartCross-Laser GX Set


Compact green cross-line laser with excellent visibility, 1/4" thread and versatile clamping bracket - recycled material is used for sustainability

This cross-line laser projects a highly visible green laser cross for precise horizontal and vertical alignment of objects. It also offers a manual slope function for easy creation of gradients and a 1/4" thread for mounting on a tripod or the supplied clamping bracket. This enables optimal use of the laser in interior fitting work and allows rapid adjustment of position and height. It can be fixed in place on site without damaging surfaces. The laser can also be used for outdoor applications and alignment work at long distances with the integrated hand-held receiver mode. The housing of the device is made from a large proportion of recycled plastic and makes a valuable contribution to sustainability.

- Sustainable design: large proportion of the housing is made from recycled plastic
- Accurate horizontal and vertical alignment of objects
- Good visibility through green laser technology
- Easy alignment of slopes with manual tilt function
- Versatile damage-free mounting options
- Height and position of the measuring device easily adjustable
- Time-saving automatic alignment
- Integrated hand-held receiver mode for outdoor applications
- Visual signals indicate when the device is outside its self-leveling range
- Pendulum restraint for safe transport

### TECHNICAL DATA

<b>Self-levelling Range</b>	± 4°
<b>Accuracy</b>	±0.3 mm/m
<b>Levelling</b>	automatic
<b>Visibility (Typical)*</b>	40 m
<b>Laser Wavelength</b>	515 nm
<b>Laser Class</b>	2 / < 1 mW
<b>Power Supply</b>	2 x 1.5V LR6 (AA)
<b>Operating Time</b>	approx. 6 hours
<b>Operating Conditions</b>	-10°C ... 50°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level
<b>Storage Conditions</b>	-20°C ... 70°C, max. humidity 85% rH
<b>Dimensions (W x H x D)</b>	84 mm x 76 mm x 62 mm
<b>Weight</b>	276 g (incl. battery)



Optional: RangeXtender G 30  
Artikel-Nr.: 033.26E

max.  
30 m



### SCOPE OF DELIVERY



Item No. 036.731E

GTIN (EAN) 4021563731794

SU 1