## Laserliner



## VideoFlex G4 Vario

## Professional video inspection system stepwise adjustable swivel range

This professional video inspection system allows hard-to-reach places, such as in pipes, wall cavities and motor vehicles to be visually inspected. Intuitive rotation of the base unit provides the user with easy spatial orientation. The efficient LED object lighting ensures reliable image capture, even in poor conditions. The camera head with a stepwise adjustable swivel range of 180° allows optimum adaptation to the location where it is to be used. The true colour reproduction provides an extremely realistic image and details can be clearly captured using the zoom function. The ergonomically designed device fits well in the hand and is also comfortable to use, even after extended periods of work. With eight languages and an exchangeable camera unit, this device can be used in many different application areas. Images and videos can be saved on an SD memory card and analysed via the USB-C interface.

- Effective problem localisation behind or in objects, walls, pipes, cavities
- SmartView: Intuitive rotation of the base unit for easy spatial orientation

TECHN	IICAL	DATA

TECHNICAE DAIA		
Diameter Camera Head	17 mm	
Camera Resolution	640 x 480 pixels	
Field of View (FOV)	73°	
Depth of Focus (DOF)	3 7 cm	
Screen Type	3,5" Colour TFT	
Display Resolution	320 x 240 pixels	
Image Format	JPEG	
Length of Probe	1.5 m	
Illumination	5 brightness levels	
Digital Zoom	2x digital zoom in 20% increments	
Memory	Micro-SD memory card up to 16 GB	
Port	USB	
Ports	USB type C RCA video output	
Power Supply	USB type C 5V / 2A Li-ion battery pack 3.7V / 2.8Ah	
Dimensions (W x H x D)	181 mm x 207 mm x 96 mm	
Weight	342 g (incl. battery pack)	

